

## STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

## NOTES:

- 1 IF PLATFORM SIZE IS REDUCED, THEN THE BLOCKING IS TO BE POSITIONED SUCH THAT IT IS CENTERED ON THE PLATFORM.

  (PLATFORM DEPTH / 2) + 2" = CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN. 28" DIMENSION)
- (2) CAR TO WALL (CTW) DIMENSION IS 3-1/2" MIN.
- 3 HOISTWAY DOORS & FRAMES MUST BE INSTALLED TO COMPLY WITH THE AUTHORITY HAVING JURISDICTION REQUIREMENTS.
  THESE DIMENSIONS VARY. CONSULT YOUR
  RESIDENTIAL ELEVATORS SALES REPRESENTATIVE
  FOR DETAILS PRIOR TO CONSTRUCTION.
- (4) HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- (5) CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN.
- (6) MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX

All Traction Elevators require an access panel for emergency lowering.

Access panel size and location must be discussed with your

Residential Elevators Sales Representative prior to construction.

